


# GZH HUNPBACK WHALE MINING HYDRAULIC POWER UNIT



Mining hydraulic power unit GZH-HUMPBACK WHALE is adapted to work in methane and nonmethane mines, excavations with degree of "a", "b" and "c" of methane explosion hazard and excavations with class of "A" and "B" of coal dust explosion hazard.

This device has been classified as Group I, category M2 due to its application in areas exposed to danger of explosion. This device has been classified as Group I, category M2 due to its application in areas exposed to danger of explosion (according to directive 2014/34/UE).

SIGMASA.pl


#### **COMPREHENSIVE IMPLEMENTATION**


OF NEW SOLUTIONS


#### **GZH-HUMPBACK WHALE**

MINING HYDRAULIC POWER UNIT

## DIAGRAM







### **TECHNICAL CHARACTERISTICS**

2

4

HYDRAULIC POWER SUPPLY [1] UNIT CAPACITY	200
WORKING PRESSURE [MPa]	21
PRESSURE'S ADJUSTMENT [MPa] RANGE	2 – 21
PRODUCTIVITY [I/min]	90
SYNCHRONOUS MOTOR ROTATIONS [rpm]	1500
ELECTRIC MOTOR'S POWER [kW]	30
VOLTAGE [V]	500 or 1000
TYPE OF HYDRAULIC OIL	oil HL-46, LHP-46, L-LH acc. to. PN-C-96057-04:1991 or other with similar parameters

OIL TEMPERATURE [°C]	- 15 to + 80
COOLING AGENT	water
MAX. COOLING AGENT'S PRESSURE [MPa]	1.2
FILTRATION ACCURACY [µm]	20
WEIGHT [kg]	~ 702
WEIGHT OF UNIT WITH OIL [kg]	~ 874

